
SECTION1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code : STARCH SPRAY BRIX
Trades code : 00955

1.2. Relevant identified uses of the substance or mixture and uses advised against

Primer

Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Bergen s.r.l.
Via Roma, 90
37060 Castel d'Azzano (Verona)
Tel. +39 045 512090 - 045 518009
Fax. +39 045 512777
e-mail: info@bergen.it
www.bergen.it

Responsible person for this MSDS: zagofab@iperv.it

Produced by
BERGEN s.r.l.
Via Roma, 90
37060 Castel d'Azzano (Verona)

1.4. Emergency telephone number

Centro Antiveleni Ospedale Riuniti (BG) - 800.883300 24 ore su 24

SECTION2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Directive 1999/45/EEC:

Classification:
F+; R12

Nature of special risks attributed:
R12 - Extremely flammable.

The product ignites easily even at temperatures below 10 °C.

The repeated inhalation of vapors can cause drowsiness and giddiness.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

2.2. Label elements

Labeling according to Directive (EC) No 1999/45:


Provided symbols:

F+ - Extremely flammable

Attributed risk:

R12 - Extremely flammable.

Precautionary statements:

S2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition — No smoking.

S23 - Do not breathe vapour/spray

S29/56 - Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

S33 - Take precautionary measures against static discharges.

S46 - If swallowed, seek medical advice immediately and show this container or label.

S51 - Use only in well-ventilated areas.

Contains:

, Perfume: It can produce an allergic reaction.

WARNINGS :

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn, even after usage. Do not spray on a naked flame or incandescent material.

Keep away from any fuel source - No smoking. Keep out of reach of children.

2.3. Other hazards

The substance / mixture does NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

SECTION3. Composition/information on ingredients
3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of risk phrases and hazard statements

mixture: n-Butane + i-Butane + Propane contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8)

| Substance | Concentration | Classification | Index | CAS | EINECS | REACH |
|--|---------------|--|--------------|------------|-----------|----------------------|
| mixture: n-Butane + i-Butane + Propane | > 10 <= 20% | F+; R12 Flam. Gas 1, H220; Liq. Gas, H280 | 649-199-00-1 | 68476-40-4 | 200-681-4 | 01-21194865 57-22 |
| Siloxanes emulsion | > 0,1 <= 1% | Xi; R43 Skin Sens. 1, H317 | N.A. | N.A. | N.A. | N.A. |
| Perfume | > 0,1 <= 1% | Xi; R43 N; R51/53 Skin Sens. 1, H317; Aquatic Chronic 2, H411 | N.A. | N.A. | N.A. | N.A. |

SECTION4. First aid measures
4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):
Wash thoroughly with soap and running water.

Direct contact with eyes (of the pure product):
Wash immediately and thoroughly with running water for at least 10 minutes.

Ingestion:
Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

If you experience harmful symptoms, contact a physician immediately.

SECTION5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:
Water spray, CO₂, foam, dry chemical, depending on the materials involved in the fire.
CO₂ or dry powder extinguisher

Extinguishing means to avoid:
Direct jets of water

5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.
Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

5.3. Advice for firefighters

Use protection for the breathing apparatus
Safety helmet and full protective suit.
The spray water can be used to protect the people involved in the extinction
You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)
Keep containers cool with water spray

SECTION6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:
Leave the area surrounding the spill or release. Do not smoke
Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.
Wear gloves and protective clothing

6.1.2 For emergency responders:
Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear gloves and protective clothing

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors. See also paragraph 8 below.

At work do not eat or drink.

Do not smoke at work

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

Keep away from flames and spark. Avoid static discharges.

7.3. Specific end use(s)

Private households (= general public = consumers):

Store in cool and dry places.

Public domain (administration, education, entertainment, services, craftsmen):

Handle with care.

Store in ventilated place away from heat sources,

Keep the container tightly closed.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

No data available on the mixture.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane
TLV-TWA (8h) 1000 ppm ACGIH (2006 Edition)

Siloxanes emulsion
Ottametilciclotetrasilossano (556-67-2): 10 ppm TWA recommendation Dow Corning.
Decametilciclopentasilossano (541-02-6): TWA 10 ppm recommendation by Dow Corning.

Perfume
No data available.

8.2. Exposure controls

Appropriate engineering controls:
Private households (= general public = consumers):
Open with caution. Close the container immediately after its use.
Adopt the appropriate protective measures.

Public domain (administration, education, entertainment, services, craftsmen):
Open with caution. Close the container immediately after its use.
Adopt the appropriate protective measures.

Individual protection measures:

(a) Eye / face protection
Wear safety goggles to EN-166

(b) Skin protection

(i) Hand protection
Not needed for normal use.

(ii) Other
Avoid direct contact with the skin
Better is to use cotton antistatic clothing

(c) Respiratory protection
Work in a sufficiently ventilated to avoid inhaling the product.

(d) Thermal hazards
No hazard to report

Environmental exposure controls:
Use according to good working practices to avoid pollution into the environment.

SECTION9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical and chemical properties | Value | Determination method |
|--|---|----------------------|
| Appearance | Pressure vessel with base and liquefied gas. | |
| Odour | Characteristic | |
| Odour threshold | not determined | |
| pH | irrelevant | |
| Melting point/freezing point | not determined | |
| Initial boiling point and boiling range | not determined | |
| Flash point | not determined | |
| Evaporation rate | irrelevant | |
| Flammability (solid, gas) | not determined | |
| Upper/lower flammability or explosive limits | for the propellant: 9.5% UEL / 1.8% LEL | |
| Vapour pressure | not determined | |
| Vapour density | not determined | |
| Relative density | 1.01-1.03 at 20 °C | |
| Solubility | water soluble base | |
| Water solubility | water soluble base | |
| Partition coefficient: n-octanol/water | not determined | |
| Auto-ignition temperature | 405 °C | |
| Decomposition temperature | not determined | |
| Viscosity | not determined | |
| Explosive properties | Lower explosion limit of the propellant: 1.8% | |
| Oxidising properties | not determined | |
| Container volume | 650 ml | |
| Product volume | 500 ml | |
| Pressure to 20°C | 3.8 - 4.2 bar | |
| Deformation pressure | not determined | |
| Burst pressure of the container | not determined | |
| Flash point of liquid phase | not determined | |
| Propellant inflammability | below 0 °C | |

9.2. Other information

No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Take precautionary measures against static discharges.

The aerosol product is stable for a period of more than 36 months and under normal storage conditions may not be dangerous reactions because the container is hermetically sealed.

Avoid contact with oxidizing materials. The product may ignite.

Avoid heat, open flames, sparks and hot surfaces.

In order to avoid that the metal of the container can deteriorate, keep away from acid reaction products or basica.

Attention to heat because at temperatures exceeding 50 °C there is an increase in pressure inside the container such as to reach the deformation of the tank until the outbreak.

10.5. Incompatible materials

Incandescent bodies, oxidizing materials.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

No toxicological tests have been performed on the mixture.

- (a) acute toxicity: not applicable
- (b) irritation: not applicable
- (c) corrosivity: not applicable
- (d) sensitisation: not applicable
- (e) repeated dose toxicity;: not applicable
- (f) carcinogenicity: not applicable
- (g) mutagenicity: not applicable
- (h) toxicity for reproduction: not applicable

Related to contained substances:

mixture: n-Butane + i-Butane + Propane

Toxicity:

Not-toxic but simple suffocating. Gaseous state has no effect on the skin and mucous membranes. The vapours may cause narcotic effects.

Irritating power:

The contact of the liquid product on the skin causes cold sores.

There is no evidence relating to the following effects: Chronic toxicity - Sensitization - Mutagenesis - Teratogenesis - Carcinogenesis.

Siloxanes emulsion

Contact with eyes: slightly irritating.

Skin contact: repeated contact can cause sensitization and allergic dermatitis.

Other health-threatening effects: recent results followed a two-year study on rats which have been exposed to repeated inhalation of vapours of octametilciclotetrasilossano (D4), reveal the effects (of benign uterine adenomas) in the wombs of females. These effects, which turned out to be specific to mice, occur only at high exposure dosage (700 ppm), a level that significantly exceeds the regular working or consumer exposures. An industrial, commercial or personal product containing D4, it constitutes a risk to humans.

Perfume

No toxicological tests have been performed on the product.

SECTION 12. Ecological information

12.1. Toxicity

The product has not been tested for environmental impact in the event of accidental release in the environment.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane
No data available

Siloxanes emulsion
No adverse effect on aquatic organisms.

Perfume
No data available.

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

No data available on the mixture.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane
No data available

Siloxanes emulsion
The siloxanes are separated by sedimentation or water absorption in waste sludge. The siloxanes degrade in the soil.

Perfume
No data available.

12.3. Bioaccumulative potential

No data available on the mixture.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane
No data available

Siloxanes emulsion
No potential to bioaccumulate.

Perfume
No data available.

12.4. Mobility in soil

No data available on the mixture.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane
No data available

Siloxanes emulsion
They are removed more than 90% by adsorption in activated sludge plant treatment. No negative effects on bacteria. Siloxanes' content in this product do not contribute to the BOD.

Perfume

No data available.

12.5. Results of PBT and vPvB assessment

The substance / mixture does NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

12.6. Other adverse effects

No adverse effects

SECTION13. Disposal considerations

13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 ° C can burst.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

SECTION14. Transport information

14.1. UN number

1950

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg



14.2. UN proper shipping name

AEROSOL flammable

14.3. Transport hazard class(es)

Class : 2

Label : 2.1

Tunnel restriction code : D

Limited quantities : 1 L

EmS : F-D, S-U

14.4. Packing group

--

14.5. Environmental hazards

Product is not environmentally hazardous

Marine polluting agent : Not

14.6. Special precautions for user

The transport must be carried out by authorised vehicles carrying dangerous goods in accordance with the requirements of the current edition of A.D.R Agreement. and the national provisions applicable.

The transport must be carried out in the original packaging and in packages that are made from materials resistant from the content and not likely to generate with this dangerous reactions. Attendants to the loading and unloading of dangerous goods must have received proper training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Legislative Decree no. 3/2/1997 no. 52 (Classification, packaging and labeling of dangerous substances). Legislative Decree 14.3.2003 n. 65 (Classification, packaging and labeling of dangerous substances). Leg. 02/02/2002 n. 25 (Risks related to chemical agents at work). D.M. Working 26/02/2004 (Occupational exposure limit); DM 04/03/2007 (Implementation of Directive no. 2006/8/EC). Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n.790/2009.D.Lgs. September 21, 2005 n. 238 (Seveso Ter).

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information

16.1. Other information

Description of the sentences of risk set out in paragraph 3

- R12 = Extremely flammable.
- R23 = Toxic by inhalation.
- R24 = Toxic in contact with skin.
- R25 = Toxic if swallowed.
- R34 = Causes burns.
- R43 = May cause sensitization by skin contact.
- R50 = Very toxic to aquatic organisms.
- R51 = Toxic to aquatic organisms.
- R53 = May cause long-term adverse effects in the aquatic environment.

Description of the hazard statements exposed to point 3

- H220 = Extremely flammable gas.
- H280 = Contains gas under pressure; may explode if heated.
- H317 = May cause an allergic skin reaction.
- H411 = Toxic to aquatic life with long lasting effects.
- H301 = Toxic if swallowed.
- H311 = Toxic in contact with skin.
- H314 = Causes severe skin burns and eye damage.
- H331 = Toxic if inhaled.
- H400 = Very toxic to aquatic life.
- H410 = Very toxic to aquatic life with long lasting effects.

Classification based on data of all mixture components

Main normative references:

- Directive 1999/45/EC
- Directive 2001/60/EC
- Regulation 1272/2008/EC
- Regulation 2010/453/EC

*** This Board cancels and replaces any previous edition.
