

---

## **SECTION1. Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

Product code : SCHIUMA SQUARE PARTY 150ml  
Trades code : 00990

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

JOKE FOAM  
Private households (= general public = consumers)[SU21]

Uses advised against  
Do not use for purposes other than those listed

### **1.3. Details of the supplier of the safety data sheet**

Bergen s.r.l.  
Via Roma, 90  
37060 Castel d'Azzano (Verona)  
Tel. +39 045 512090 - 045 518009  
Fax. +39 045 512777  
e-mail: info@bergen.it  
www.bergen.it

Persona competente responsabile della scheda di dati di sicurezza: zagofab@iperv.it

Produced by  
BERGEN s.r.l.  
Via Roma, 90  
37060 Castel d'Azzano (Verona)

### **1.4. Emergency telephone number**

Centro Antiveneni Ospedale Riuniti (BG) - 800.883300 24 ore su 24

---

## **SECTION2. Hazards identification**

### **2.1. Classification of the substance or mixture**

2.1.1 Classification according to Directive 1999/45/EEC:

Classification:  
Nonhazardous

Nature of special risks attributed:

None in particular.

The repeated inhalation of vapors can cause drowsiness and giddiness.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

### **2.2. Label elements**

Labeling according to Directive (EC) No 1999/45:

Provided symbols:  
No hazard symbol expected

---

**Attributed risk:**

The product does not introduce specific risks.

**Precautionary statements:**

S2 - Keep out of the reach of children.

S23 - Do not breathe spray

S51 - Use only in well-ventilated areas.

**WARNINGS :**

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn even after use. Keep out of reach of children.

5 % of total components in term of mass is flammable

Safety data sheet available for professional user on request

**2.3. Other hazards**

The substance / mixture does NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

**SECTION3. Composition/information on ingredients****3.1 Substances**

Irrilevant

**3.2 Mixtures**

Refer to paragraph 16 for full text of risk phrases and hazard statements

mixture: n-Butane + i-Butane + Propane contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8)

Substance	Concentration	Classification	Index	CAS	EINECS	REACH
mixture: n-Butane + i-Butane + Propane	> 1 <= 5%	F+; R12 Flam. Gas 1, H220; Liq. Gas, H280	649-199-00-1	68476-40-4	200-681-4	01- 2119486557- 22
Coconut diethanolamide	> 1 <= 5%	Xi; R38 Xi; R41 Skin Irrit. 2, H315; Eye Dam. 1, H318	N.A.	68603-42-9	271-657-0	

**SECTION4. First aid measures****4.1. Description of first aid measures****Inhalation:**

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

**Direct contact with skin (of the pure product):**

Wash thoroughly with soap and running water.

**Direct contact with eyes (of the pure product):**

Wash immediately and thoroughly with running water for at least 10 minutes.

**Ingestion:**

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

---

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

If you experience harmful symptoms, contact a physician immediately.

---

**SECTION5. Firefighting measures**

**5.1. Extinguishing media**

Advised extinguishing agents:

Water spray, CO<sub>2</sub>, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing means to avoid:

Direct jets of water

**5.2. Special hazards arising from the substance or mixture**

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance ( protect the head using a safety helmet).

**5.3. Advice for firefighters**

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

---

**SECTION6. Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

Wear gloves and protective clothing

6.1.2 For emergency responders:

Given the tightness of aerosol, it is unlikely that the spillage may occur.

However if some container is damaged likely to cause a loss, insulate the tank in question by bringing it to open air or covering it with inert material and fuel (eg sand, earth, vermiculite) and having the care to avoid any point of ignition that might pose a serious risk of fire.

Wear gloves and protective clothing

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

**6.2. Environmental precautions**

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

---

### **6.3. Methods and material for containment and cleaning up**

#### 6.3.1 For containment:

Recover the product for reuse, if possible, or the removal.

#### 6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

#### 6.3.3 Other information:

None in particular.

### **6.4. Reference to other sections**

Refer to paragraphs 8 and 13 for more information

## **SECTION 7. Handling and storage**

### **7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors. See also paragraph 8 below.

At work do not eat or drink.

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

Store in a cool place, away from sources of heat and direct exposure of sunlight.

### **7.3. Specific end use(s)**

Private households (= general public = consumers):

Store in cool and dry places.

## **SECTION 8. Exposure controls/personal protection**

### **8.1. Control parameters**

No data available on the mixture.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane

TLV-TWA (8h) 1000 ppm ACGIH (2006 Edition)

Coconut diethanolamide

No data available.

### **8.2. Exposure controls**

Appropriate engineering controls:

Private households (= general public = consumers):

Open with caution. Close the container immediately after its use.

Adopt the appropriate protective measures.

**Individual protection measures:**

- (a) Eye / face protection  
Wear safety goggles to EN-166
- (b) Skin protection
  - (i) Hand protection  
Not needed for normal use.
  - (ii) Other  
Avoid direct contact with the skin  
Better is to use cotton antistatic clothing
- (c) Respiratory protection  
Work in a sufficiently ventilated to avoid inhaling the product.
- (d) Thermal hazards  
No hazard to report

**Environmental exposure controls:**

Use according to good working practices to avoid pollution into the environment.

**SECTION 9. Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Physical and chemical properties	Value	Determination method
Appearance	Container with base and liquefied gases	
Odour	characteristic	
Odour threshold	not determined	
pH	9.98 at 25 °C	
Melting point/freezing point	not determined	
Initial boiling point and boiling range	not determined	
Flash point	not determined	ASTM D92
Evaporation rate	irrelevant	
Flammability (solid, gas)	not determined	
Upper/lower flammability or explosive limits	for the propellant: 9.5% LEL/UEL 1.8%	
Vapour pressure	not determined	
Vapour density	not determined	
Relative density	0.936	
Solubility	water soluble base	
Water solubility	water soluble base	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	405 °C	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	not explosive	
Oxidising properties	non-oxidizing	
Container volume	210 ml / 335 ml	
Product volume	150 ml / 250 ml	

Physical and chemical properties	Value	Determination method
Pressure to 20°C	3.8 - 4.2 bar	
Deformation pressure	not determined	
Burst pressure of the container	not determined	
Flash point of liquid phase	not determined	
Propellant inflammability	less than 0 °C	

## 9.2. Other information

No data available.

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

No reactivity hazards

### 10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

### 10.3. Possibility of hazardous reactions

There are no hazardous reactions

### 10.4. Conditions to avoid

Take precautionary measures against static discharges.

The aerosol product is stable for a period of more than 36 months and under normal storage conditions may not be dangerous reactions because the container is hermetically sealed.

Avoid contact with oxidizing materials. The product may ignite.

Avoid heat, open flames, sparks and hot surfaces.

In order to avoid that the metal of the container can deteriorate, keep away from acid reaction products or basica.

Attention to heat because at temperatures exceeding 50 °C there is an increase in pressure inside the container such as to reach the deformation of the tank until the outbreak.

### 10.5. Incompatible materials

Incandescent bodies, oxidizing materials.

### 10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11. Toxicological information

### 11.1. Information on toxicological effects

No toxicological tests have been performed on the mixture.

(a) acute toxicity: not applicable

(b) irritation: not applicable

- (c) corrosivity: not applicable
- (d) sensitisation: not applicable
- (e) repeated dose toxicity: not applicable
- (f) carcinogenicity: not applicable
- (g) mutagenicity: not applicable
- (h) toxicity for reproduction: not applicable

Related to contained substances:

mixture: n-Butane + i-Butane + Propane

Toxicity:

Not-toxic but simple suffocating. Gaseous state has no effect on the skin and mucous membranes. The vapours may cause narcotic effects.

Irritating power:

The contact of the liquid product on the skin causes cold sores.

There is no evidence relating to the following effects: Chronic toxicity - Sensitization - Mutagenesis - Teratogenesis - Carcinogenesis.

Coconut diethanolamide

Oral LD50 rat: > 2,000 mg/kg

Dermal LD50 rat: > 2,000 mg/kg

Eye contact: irritating to the eye (rabbit). Can cause irreversible damage to the eye; (value of literature).

Skin contact: moderately irritating for a single application (4 h-rabbit); (value of literature).

Sensitization: Guinea pig Maximisation Test: not a sensitizer; (value of literature).

Genotoxicity: in vitro Ames method; not mutagenic; (value of literature).

## SECTION12. Ecological information

### 12.1. Toxicity

The product has not been tested for environmental impact in the event of accidental release in the environment.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane

No data available

Coconut diethanolamide

Fish toxicity, LC50, 1-10 mg/l (DIN EN ISO 7346-2)

Use according to good working practices to avoid pollution into the environment.

### 12.2. Persistence and degradability

No data available on the mixture.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane

No data available

Coconut diethanolamide

Primary: Biodegradability > 90% (OECD)

Easy Biodegradability: 60% > (manometric Tests, O<sub>2</sub> consumption)

Theoretical O<sub>2</sub> demand (thod): 2.52 mg O<sub>2</sub>/mg.

Chemical O<sub>2</sub> demand (COD): 2.51 mg O<sub>2</sub>/mg.

---

### **12.3. Bioaccumulative potential**

No data available on the mixture.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane  
No data available

Coconut diethanolamide  
No data available

### **12.4. Mobility in soil**

No data available on the mixture.

Related to contained substances:

mixture: n-Butane + i-Butane + Propane  
No data available

Coconut diethanolamide  
No data available

### **12.5. Results of PBT and vPvB assessment**

The substance / mixture does NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

### **12.6. Other adverse effects**

No adverse effects

---

## **SECTION13. Disposal considerations**

### **13.1. Waste treatment methods**

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 ° C can burst.

Recover if possible. Operate according to local or national regulations

---

## **SECTION14. Transport information**

### **14.1. UN number**

Not included in the scope of application regulations concerning the transport of dangerous goods: by road (ADR); by rail (RID); by air (ICAO / IATA); by sea (IMDG).

### **14.2. UN proper shipping name**

None

### **14.3. Transport hazard class(es)**

None

---



**14.4. Packing group**

None

**14.5. Environmental hazards**

None

**14.6. Special precautions for user**

No data available.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

It is not intended to carry bulk

---

**SECTION15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Legislative Decree no. 3/2/1997 no. 52 (Classification, packaging and labeling of dangerous substances). Legislative Decree 14.3.2003 n. 65 (Classification, packaging and labeling of dangerous substances). Leg. 02/02/2002 n. 25 (Risks related to chemical agents at work). D.M. Working 26/02/2004 (Occupational exposure limit); DM 04/03/2007 (Implementation of Directive no. 2006/8/EC). Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n.790/2009.D.Lgs. September 21, 2005 n. 238 (Seveso Ter).

**15.2. Chemical safety assessment**

No chemical safety assessment was carried out by the supplier

---

**SECTION16. Other information**

**16.1. Other information**

Description of the sentences of risk set out in paragraph 3

- R12 = Extremely flammable.
- R38 = Irritating to skin.
- R41 = Risk of serious damage to eyes.

Description of the hazard statements exposed to point 3

- H220 = Extremely flammable gas.
- H280 = Contains gas under pressure; may explode if heated.
- H315 = Causes skin irritation.
- H318 = Causes serious eye damage.

Classification based on data of all mixture components

Main normative references:

- Directive 1999/45/EC
- Directive 2001/60/EC
- Regulation 1272/2008/EC
- Regulation 2010/453/EC

\*\*\* This Board cancels and replaces any previous edition.

---